

NEW PRODUCT



INFORMATION

11020N Battery Operated 20L Oil Drum Pump



For Warranty Policies & Terms and Conditions refer to our website:

www.alemlube.com.au

August 2026

The Alemlube 11020N Battery Operated 20L Oil Drum Pump enables quick and effortless oil & vehicle fluids transfer and improves efficiency and productivity in busy workshops – your time creator and energy saver.

The kit is supplied with a rechargeable battery that has a fully charged run time of up to 65 minutes[†] and is suitable for the transfer of engine oil, gear oil, hydraulic oil, transmission fluid, coolant & diesel.

The Alemlube 11020N has a delivery rate of up to 4.3L per minute[†] & is designed and engineered with performance, durability and serviceability front of mind.

The 11020N will operate reliably even in challenging and arduous conditions.

The pump can deliver up to 280L[†] before recharging of the battery is required with a fast recharge time of 45 minutes. The quick connect, disconnect motor can be used on multiple pumptube assemblies, thereby reducing upfront set up costs.

Package includes:

- 11000MA[#] Modular motor assembly (IK10 rated)
- 11000B[#] 21.6V Li-ion battery (IK9 rated)
- 11000BC[#] 240V battery charger
- 1.5m x 19mm ID long delivery hose & control valve

Also available:

11020PTAN 20L Oil Drum Pumptube Assembly

11205N Battery Operated 205L Oil Drum Pump

11205PTAN 205L Oil Drum Pumptube Assembly

SPECIFICATIONS, FEATURES & BENEFITS

- Suitable for pumping engine oil, hydraulic oil, gear oils up to SAE 140, transmission fluid, coolant & diesel
- High impact resistant IK10 rated motor assembly resists operator misuse
- IP42 rated motor is fully & easily serviced with individual spare parts and kits readily available
- Three point pumptube to motor locking system is robust & durable
- Steel to steel impeller priming system minimises current draw and maximises battery operating time per charge
- Thermal protection set at 90°C cuts in if the motor is left running and overheats
- Transfers up to 280L per battery charge[†]
- Flow rates of up to 4.3L/min[†]
- Battery run time of up to 65 min[†]
- Battery recharge time of 45 min
- Carry handle assists with drum changeovers
- Battery includes a battery level display
- Battery can be changed without needing to disconnect and reconnect the motor from the pumptube
- On/off oil control valve can be locked open if required
- Swivelling pump head eliminates the chance of hose kinks
- Drainback nozzle holster ensures that excess oil ends up in the drum & not on your workshop floor

[†] All flow rate and delivery figures based on 5W-30 engine oil.

[#] Designed for use with the 11000N Series.

www.alemlube.com.au

www.alemlube.co.nz

NSW/ACT (02) 9677 1555

QLD/PNG (07) 3491 2600

VIC/TAS (03) 8787 8288

WA (08) 9302 4199

SA/NT (08) 8241 7111

NZ (09) 447 1007