

FA2**Alemlube 1" BSP(f) Fuel Filter**

September 2026

The Alemlube 1" BSP(f) fuel filter is designed for inline use with gravity feed tanks, hand pumps, & electric fuel pumps.

It features a lightweight die-cast aluminium head & a translucent plastic bowl which are both compatible for use with diesel, standard grades of petrol, and ethanol/biodiesel blends up to 20%.

With its 10-micron filter & 2,360cm² of filter surface for maximum filtration, the FA2 removes microscopic particles such as rust, dirt, sand, & water from fuels and is suitable for applications with a maximum working pressure of 150psi.

It's also capable of filtering fuel at a rate of 19 litres per minute with gravity flow tank applications & a maximum flow rate of up to 100 litres per minute with hand and electric pumps.

The FA2 is not recommended for water-based products, aviation fuels, race fuels, or petrol with more than a 10% ethanol content.

SPECIFICATIONS, FEATURES & BENEFITS

- Alemlube fuel filter with replaceable clear plastic bowl
- Suitable for diesel, standard grades of petrol, & ethanol/biodiesel blends up to 20%
- For use with gravity feed applications & pumps up to 100L/min
- 1" BSPT(f) inlet & outlet thread
- 10-micron fuel filter element
- 2,360cm² of filter surface for max filtration
- Rated to a maximum working pressure of 150psi
- Replacement element PF10N readily available